



38898

SunSaver MPPT 15 A Charge Controller for 12 or 24 V Batteries



A Charge Controller Designed for Large Solar Panels

Overview

The 38898 consists of a Morningstar 15 A charge regulator that has been re-configured by Campbell Scientific and includes the mounting hardware to mount it to a 2.54 cm (1 in.) grid back panel. This charge controller is well suited for large solar

panels, such as the [SP305-L 305 W Solar Panel](#). As an additional benefit, Campbell Scientific provides full support of the SunSaver MPPT.

Benefits and Features

- › 12 V or 24 V battery charging
- › 60 Vdc maximum input compared with the 50 Vdc on the CH201 and 40 Vdc on the CH150
- › Selectable battery type: gel, sealed, AGM, flooded
- › Programmable low voltage disconnect (LVD)
- › Auto-equalize feature for flooded battery only
- › Terminals for remote temperature sensor (RTS) to compensate charging based on battery temperature; use pn 38899
- › Built-in temperature sensor for use when no RTS is provided
- › Battery status LEDs to provide battery state of charge and indicate fault condition
- › RS-232 communication with pn 34540

Detailed Description

The 38898 uses maximum power point tracking. While the 38898 is capable of RS-232, Modbus, and USB communications, only RS-232 communication is supported through the hardware. *Note:* When reading parameters off the 38898 using a data logger, you must use the CPI/RS-232 port. This functionality does not work when using the control ports.

The 38898 offers the ability to select the battery type: gel, sealed, AGM, or flooded. To set the battery type, use a jumper and switch #1.

The 38898 offers programmable low voltage disconnect (LVD). From the manufacturer, the 38898 comes with an 11 V LVD when switch #2 is on and an 11.5 V LVD when switch #2 is off. At Campbell Scientific, we prioritize data over battery health and reconfigure the LVD to 6 Vdc when switch #2 is on, and we ship the 38898 with switch #2 on. When switch #2 is off, an LVD of 11.5 Vdc is used. *Caution:* Draining a battery below 11.5 V will shorten the life of the battery.

Specifications

Operational Temperature	-40° to +60°C
Storage Temperature	-55° to +100°C
Battery Voltage Range	7 to 36 V (power out)
Maximum Input Voltage	60 V
Quiescent Current	35 mA
Certifications	› Manufactured in a certified ISO 9001 facility. › IEC 62109

- › ETL Listed (UL-1741 and Canadian CSA C22.2 No.107.1.01)
- › FCC Class B Part 15 compliant
- › CE and RoHS

Dimensions	› 6.43 x 19.1 x 7.26 cm (2.53 x 7.52 x 2.86 in.) with mount foot › 6.43 x 16.89 x 7.26 cm (2.53 x 6.65 x 2.86 in.) without mount foot
------------	--

Weight	589.67 g (1.3 lb)
--------	-------------------

For comprehensive details, visit: www.campbellsci.com/38898 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Inc. | 11/05/2020